

99 mm

R = 7.6 mm

**ACTEV BATTERY ADAPTER INSTRUCTIONS**

---

**The Battery Adapter can be used two ways:**

- Charging a battery when both a battery and charger are connected
- Displaying a battery's state-of-charge when only a battery is connected

**Approximate charging times for a fully-discharged battery:**

	STANDARD BATTERY	DOUBLE CAPACITY BATTERY
STANDARD CHARGER	10 HOURS	18 HOURS
RAPID CHARGER	105 MINUTES	200 MINUTES

A flashing bottom LED indicates a battery fault.  
Contact Actev Motors at [support@actevmotors.com](mailto:support@actevmotors.com) 7100-0014\_RevB

71mm

**⚠ BATTERY AND CHARGER WARNINGS**

---

Lithium-Ion batteries contain hazardous chemicals and store considerable energy. Observe the following rules to prevent fire, explosion or serious injury:

- Observe all safety warnings on the battery label.
- Use only Actev Motors Lithium-Ion Battery; use of improper battery could cause **FIRE** and **EXPLOSION!**
- Misuse, modification and damage can cause Lithium-Ion batteries to **IGNITE** and **EXPLODE!**
- Use only Actev Motors Lithium-Ion Battery Chargers.
- Contact Actev Motors immediately if suspected of damage.
- Always secure battery with straps when driving.
- Battery should not be used or charged below 0°C (32°F) or above 40°C (104°F).
- Only carry the battery by holding onto the main case; do not carry by the cable.
- Never insert any objects into the battery connector.
- Do not remove the protective cover or disassemble the battery.
- Always protect the battery from damage during transportation.
- Never dent or pierce battery case.
- Clean the battery with a damp cloth; never immerse in water.

↖  
Cut Line Only  
(does not print)